



Federkennwerte für 70° Shore
bei axialer, statischer Druckbelastung.

GN 438 / GN 438.5



GN 439 / GN 439.5



| d₁ | h | Federrate ≈ in N/mm | max. Last F _A in N | max. Weg in mm |
|----------------------|----------|------------------------|----------------------------------|-------------------|
| 19 | 3 | 282 | 480 | 1,7 |
| 19 | 7 | 213 | 373 | 1,75 |
| 19 | 14 | 68 | 240 | 3,5 |
| 25 | 3 | 1870 | 1870 | 1 |
| 25 | 8 | 349 | 698 | 2 |
| 25 | 16 | 135 | 540 | 4 |
| 32 | 4 | 1680 | 1680 | 1 |
| 32 | 9 | 548 | 1233 | 2,25 |
| 32 | 18 | 212 | 850 | 4 |
| 38 | 4 | 1500 | 1500 | 1 |
| 38 | 10 | 704 | 1760 | 2,5 |
| 38 | 20 | 230 | 920 | 4 |
| 50 | 5 | 3600 | 3600 | 1 |
| 50 | 11 | 1223 | 3670 | 3 |
| 50 | 22 | 500 | 2500 | 5 |
| 64 | 5 | 1460 | 1460 | 1 |
| 64 | 13 | 2016 | 6050 | 3 |
| 64 | 26 | 616 | 3700 | 6 |